

HSE PRODUCT PROFILE: PIPE CLAMP MP-L-I



Standard galvanized pipe clamp with quick closure for light-duty applications for various pipe materials

Criteria	Values
Product Carbon Footprint [GWP 100 years kg CO2 eq.] (acc. to ISO 14040/44; CML 2001)	See following pages
Ozone Depleting Potential (ODP, catalytic value) [kg R11 eq.] (acc. to ISO 14040/44; CML 2001)	See following pages
Environmental Product Declaration (EPD) available	No
Free of Halogens (acc. to Supplier Declaration)	Yes
Free of Phthalates (acc. to Supplier Declaration)	Yes
REACH, PAH, RoHS conformity (acc. to Supplier Declaration)	Yes
Materials used	DC01 – DIN EN 10130 EPDM Rubber
Surface finish	Galvanised
Noise reduction	18.5 dB (A)
Manufacturing location / Country of origin	China
Recycled content (pre-consumer) (acc. to LEED standard v.4)	0% of EPDM (foam) 0% of steel
Recycled content (post-consumer) (acc. to LEED standard v.4)	0% of EPDM (foam) 25% of Steel
Recycling of packaging	Yes
Reuse of materials/ convertibility	Pipe clamps are normally used for permanent applications and remain installed there for their entire working life
End of life status	Recyclable
Footnote	Number of items per sales pack varies: 10, 25 or 50